

Phaesun DC Installation

Div • 09/2014

The equipment is developed for solar-powered (battery) installations, rating from 12V to 48V DC.

10A - 2 pole, no earth. The socket outlet coverplates are made of thermosetting plastic. This DC equipment is totally polarized, e.g. The plug will fit only one way in the outlet, assuring correct polarity at all times. Consequently the plug has one thick and one thin pin - making the polarity unmistakable. Suitable equipment onboard for ex boats, yachts, campers, in cottages, solar home systems, etc. and in areas without fully built-out electrical network, that are dependant on rechargeable batteries based on solar energy.



DC Double Surface Socket



DC Flush Type Double Surface Socket



DC Plug No Earth



DC Junction Box



Toggle Switch



Drop Light Fitting E27

Technical Data	DC Double Surface Socket	DC Flush Type Double Surface Socket	DC Plug No Earth	DC Junction Box	Toggle Switch
Electrical Parameters					
Voltage DC [V]			12 - 48		
Current [A]			10		
Material			Thermosetting Plastic		
Connection Possibilities [m²]			2 x 6 / 3 x 4 / 4 x 2,5 / 5 x 1,5		
Color			pearl white		
Dimensions (hxlxw) [mm]	100 x 65 x 26	96 x 84 x 26	36 x 50	47 x 69 x 28	63 x 63x 33
Packing Unit [pcs.]	10 / 50	10 / 50	50 / 500	10 / 50	10
Article No.	103.710	103.711	103.712	103.713	103.734