



NH FUSE ENCLOSURE

AKi-T 201



AKi-T 201

NH fuse enclosure

300 x 300 x 132 mm

Article number: 78620101

NH fuse enclosure -Industrial Quality-, IP65 (when using the corresponding cable entry), 1 x NH 00 fuse switch disconnecter, assembled on mounting plate, rated current 125 A, clamp connection 1.5 - 70 mm², N terminal 2 x 50 mm², with IP54 attachment bushes, with insulating seals

with transparent cover



Technical data

Measures

| | |
|---------|--------|
| Width: | 300 mm |
| Length: | 300 mm |
| Height: | 132 mm |

Material

| | |
|--------------|---------------------------------------|
| Base: | polycarbonate, glass fiber-reinforced |
| Cover: | Polycarbonate, transparent |
| Sealing: | Polyurethane |
| Cover screw: | Polyamide 6, fiber-glass reinforced |

Other attributes

| | |
|--------------------|------|
| Fire protection: | none |
| Heavy metals-free: | Yes |



NH FUSE ENCLOSURE

AKi-T 201

| | |
|---------------------|---|
| PVC-free: | Yes |
| Silicone-free: | Yes |
| Ingress protection: | IP65 - acc. EN 60529 / DIN VDE 0470-1 |

Environmental attributes

| | |
|--|--------|
| Ambient temperature (24 h): | 60 °C |
| Ambient temperature (max.): | 80 °C |
| Ambient temperature (min.): | -35 °C |
| Max. rel. humidity at 25° C (short Therm): | 95% |
| Max. rel. humidity at 40° C: | 50% |