

Gel Battery / Gel Batterie





Eco Store

340265, 340266, 340267, 340268, 340269, 340270 • DE/EN • 12/2019

The new Active Power Battery supports you in all your projects. The advantage of this new gel battery is its high cycle resistance. 500 cycles at 80% discharge. The battery is completely sealed. In normal use, there is no gas formation. Since no additional ventilation is required, the batteries can be installed anywhere. They are ideal as a service battery and for cyclic applications. In addition, they can be recharged very quickly. The battery is also extremely vibration resistant, completely maintenance-free and can be stored for up to 9 months.

Die neue Active-Power Batterie unterstützt Sie bei all Ihren Vorhaben. Der Vorteil dieser neuen Gel Batterie ist ihre hohe Zyklenfestigkeit. 500 Zyklen bei 80% Entladung. Damit macht diese Power Gel Batterie Ihrem Namen alle Ehre. Die Batterie ist komplett verschlossen, bei normaler Verwendung gibt es keine Gasbildung. Da keine zusätzliche Belüftung erforderlich ist, können die Batterien überall installiert werden. Sie eignen sich ideal als Service-Batterie und für zyklische Anwendungen. Zudem können sie sehr schnell wieder aufgeladen werden.



Technical Data	Technische Daten		Eco Store 70	Eco Store 90	Eco Store 100	Eco Store 140	Eco Store 165	Eco Store 235
Nominal voltage	Nennspannung	VDC	12					
Capacity	Kapazität	Ah (C5)	50	70	75	105	130	180
		Ah (C20)	60	80	85	125	150	210
		Ah (C100)	70	90	100	140	165	235
Dimensions	Abmessungen	mm	278 x 175 x 190	353 x 175 x 190	352 x 171 x 236	345 x 175 x 290	513 x 223 x 223	518x273x242
Weight	Gewicht	kg	21	26	31	40	52	71
Electrolyte density	Elektrolytdichte	kg / ltr.	1,28					
Electrolyte	Elektrolyt		Verdünnte Schwefelsäure in GEL-festgelegt diluted sulphuric acid fixed in gel					
Enclosure	Gehäuse		Graues Gehäuse PP Ventil-Stopfen grey enclosure PP vent plug					
Bottom lath	Bodenleiste			B1	-	-	-	-
Separator	Separator		Microporöser Taschenseparator microporous pocket separator					
Terminal Type	Polausführung							
Terminal position	Anschlussposition							
Degassing	Entgasung		Innere Gas-Rekombination internal gas recombination					
Delivery status	Auslieferungszustand		Gefüllt und geladen verschlossen Postversand möglich filled and charged sealed postal delivery possible					
Article No.	Artikel Nr.		340265	340266	340267	340268	340269	340270