


PC




Cu-ETP 99,9%, Sn / Copper tinned  
PC / Polycarbonate insulation  
600V max.  
T 125°C max.

DIN 46237  
(exc.: \*)



| mm <sup>2</sup> | Ø mm      | Art. N.   |      | mm  |      |      |     |      | Pack |
|-----------------|-----------|-----------|------|-----|------|------|-----|------|------|
|                 |           |           |      | d1  | d4   | d2   | d3  | l    |      |
| 0,1-0,5         | 2         | ICIQ052 * | ●    | 1   | 2,3  | 2,2  | 5   | 14,0 | 100  |
|                 | 3         | ICIQ053 * | ●    |     |      | 3,2  | 5   | 14,0 | 100  |
|                 | 4         | ICIQ054 * | ●    |     |      | 4,3  | 6,5 | 16,0 | 100  |
|                 | 5         | ICIQ055 * | ●    |     |      | 5,3  | 8   | 16,0 | 100  |
| 0,5-1           | 2         | ICIQ12    | ●    | 1,6 | 4    | 2,2  | 6   | 17,0 | 100  |
|                 | 3         | ICIQ13    | ●    |     |      | 3,2  | 6   | 17,0 | 100  |
|                 | 3,5       | ICIQ135   | ●    |     |      | 3,7  | 6   | 17,0 | 100  |
|                 | 4         | ICIQ14    | ●    |     |      | 4,3  | 8   | 18,0 | 100  |
|                 | 4         | ICIQ14S   | ●    |     |      | 4,3  | 7   | 17,5 | 100  |
|                 | 5         | ICIQ15    | ●    |     |      | 5,3  | 10  | 19,0 | 100  |
|                 | 5         | ICIQ15S   | ●    |     |      | 5,3  | 8   | 18,5 | 100  |
|                 | 6         | ICIQ16 *  | ●    |     |      | 6,5  | 10  | 19,0 | 100  |
|                 | 8         | ICIQ18 *  | ●    |     |      | 8,4  | 14  | 23,0 | 100  |
| 10              | ICIQ110 * | ●         | 10,5 | 18  | 25,0 | 100  |     |      |      |
| 1,5-2,5         | 3         | ICIQ23    | ●    | 2,3 | 4,4  | 3,2  | 6   | 17,0 | 100  |
|                 | 3,5       | ICIQ235   | ●    |     |      | 3,7  | 6   | 17,0 | 100  |
|                 | 4         | ICIQ24    | ●    |     |      | 4,3  | 8   | 18,0 | 100  |
|                 | 4         | ICIQ24S   | ●    |     |      | 4,3  | 6,8 | 17,6 | 100  |
|                 | 5         | ICIQ25    | ●    |     |      | 5,3  | 10  | 20,0 | 100  |
|                 | 5         | ICIQ25S   | ●    |     |      | 5,3  | 8   | 19,5 | 100  |
|                 | 6         | ICIQ26    | ●    |     |      | 6,5  | 11  | 22,0 | 100  |
|                 | 8         | ICIQ28    | ●    |     |      | 8,4  | 14  | 23,0 | 100  |
|                 | 10        | ICIQ210 * | ●    |     |      | 10,5 | 18  | 25,6 | 100  |
|                 | 12        | ICIQ212 * | ●    |     |      | 13,0 | 18  | 26,0 | 100  |
| 4-6             | 4         | ICIQ64    | ●    | 3,6 | 6,4  | 4,3  | 8   | 21,0 | 100  |
|                 | 5         | ICIQ65    | ●    |     |      | 5,3  | 10  | 22,0 | 100  |
|                 | 6         | ICIQ66    | ●    |     |      | 6,5  | 11  | 23,0 | 100  |
|                 | 8         | ICIQ68    | ●    |     |      | 8,4  | 14  | 26,0 | 100  |
|                 | 10        | ICIQ610   | ●    |     |      | 10,5 | 18  | 28,0 | 100  |
|                 | 12        | ICIQ612   | ●    |     |      | 13,0 | 18  | 28,0 | 100  |

typically used tools: „GENERAL CATALOG TOOLS“  6 - 16 mm<sup>2</sup> page: 136

 series 60, 130: 10 mm<sup>2</sup>≤. page: 141, 144