

Photovoltaics PV-STICK SET

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Faster is better. This also applies to the cabling of solar systems. Our handy connectors stay firmly in your grip even in frosty temperatures and can be installed very quickly and easily without a crimping tool.

You don't need crimp contacts and crimping tools and you avoid assembly errors. This saves up to 50% installation time – without affecting quality. The new photovoltaic connectors are TÜV-approved and comply with IEC 62852.

Our "PUSH IN" technology enables safe connections with minimal effort – insert, turn: current!

- 1.500 V DC (DE) / 1,500 V DC (EN)
- PUSH IN technology
- Standard-compliant quality in accordance with IEC 62852
- Ergonomic, prize-winning design
- Fastest PV connector currently available
- Reliable latching

General ordering data

Type	PV-STICK SET
Order No.	1422030000
Version	Photovoltaics, Plug-in connector, PUSH IN connection, Pin, Socket connector
GTIN (EAN)	4050118225723
Qty.	1 pc(s).

**Photovoltaics
PV-STICK SET**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Net weight 31.94 g

Temperatures

Operating temperature, max.	115 °C	Temperature range, installation, min.	10 °C
Continuous operating temp., min.	-40 °C	Continuous operating temp., max.	85 °C
Temperature range, installation, max.	40 °C		



Technical data

Approvals	TÜV Rheinland (IEC 62852)	Cable type	2 Pfg 1169/08.07, EN 50618:2014
Conductor cross-section, max.	6 mm ²	Conductor cross-section, min.	4 mm ²
Outer cable diameter, max.	7.5 mm	Outer cable diameter, min.	5.5 mm
Pollution severity	3 (2 within the sealed area)	Protection degree	IP65, in closed state, IP2x open
Rated current	30 A	Rated voltage	1500 V DC (IEC)

Classifications

ETIM 6.0	EC002928	ETIM 7.0	EC002928
eClass 9.0	22-57-92-03	eClass 9.1	27-44-01-07
eClass 10.0	27-44-01-07		

Approvals

Approvals  

ROHS Conform

Downloads

User Documentation [Instruction Sheet](#)