

LED Lighting Units | LED Leuchte

Airtight Single, Airtight Twin

500071, 500072, 500075, 500078 • DE/EN • 11/2021

Phaesun Airtight Lighting Units are especially designed for outdoor use. Due to the highly efficient LED tubes they provide immediate bright lighting without cold-start problems. Airtight is often combined with motion detectors. The lighting units are available in different versions.

Diese Leuchten garantieren sofort helle und effiziente Beleuchtung und eignen sich somit perfekt für Terrassen oder den Gebrauch in Kombination mit Bewegungsmeldern. Perfekt für den Gebrauch im Freien Dank IP65!



Technical Data	Technische Daten		Airtight Single 1000_12-60	Airtight Twin 2000_12-60	Airtight Single 2000_12-120	Airtight Twin 4000_12-120
Nominal voltage	Systemspannung	VDC	12 / 24			
Voltage range	Spannungsbereich	VDC	11 ... 30			
Tube size	Röhren Abmessung	cm	1 x 54	2 x 54		4 x 54
Current	Strom	A	0,8 / 0,4	1,7 / 0,85		3,4 / 1,7
Power	Leistung	W	10	20		40
Light temperature	Lichttemperatur	K	5700			
Lumen	Lumen	lm	1200	2400		4800
Efficiency	Wirkungsgrad	lm/W	100			
Ambient temp.	Umgebungstemperatur		- 20 ... + 50°C			
Lifetime	Lebensdauer	h	36000			
Beam Angle	Abstrahlwinkel		180°			
Ingress Protection	IP-Schutz		IP65			
Dimension (mm)	Abmessung (mm)	X x Y x Z	680 x 90 x 100	680 x 150 x 100	1280 x 90 x 100	1280 x 150 x 100
Weight	Gewicht	g	0,7	1,0	1,4	2,0
Protective function	Schutzfunktion		wrong polarity, over temperature Verpolung, Übertemperatur			
Article Number	Artikelnummer		500071	500072	500075	500078