

Solar Cold Room

SelfChill DC | 20 M³ | 10 °C | 250 kg/day | 35 °C

600531 • EN • 02/2024

The Solar Cold Room SelfChill DC is a kit that includes all the necessary components for the construction of a SelfChill Cold Room which is a self-sufficient system utilizing solar-powered SelfChill® Cooling Units to chill 250kg of agricultural products daily to 10°C, even in regions with ambient temperatures as high as 35°C. The system is based on the SelfChill concept, in which cold is generated by solar-powered SelfChill® Cooling Units and stored as ice in a thermal energy storage (water chiller) for efficient transfer and low losses. The heat exchanger and thermostat ensure reliable cold distribution. The adaptive control unit optimizes solar energy use and provides remote monitoring.



Technical Data	
Cold Room volume	20 m ³
Ice Storage	300 kg
Power _{electrical} (for 6 Cooling Units)	450 W
Power _{electrical} (pump + heat exchanger)	40 W
Power _{thermal} rated (@35 °C ambient temperature)	900 W
Power _{thermal} , max	3,4 kW
PV capacity (for 6 Cooling Units)	2280 Wp
PV capacity (for pump + heat exchanger)	760 Wp
Battery Capacity (for 6 Cooling Units)	525 Ah @24VDC
Battery Capacity (for pump + heat exchanger)	175 Ah @24VDC

Components	Quantity
Cold Cell 20m ³	1
PE Box with PUR Insulation and cover Phaesun SelfChill 500L	1
Water-Air heat exchanger Phaesun SelfChill 24VDC	1
Water Chiller with shelves, pipes, valves, pump etc.	1
Solar Cooling Unit SelfChill Direct-Drive MT 75Upgrade	6
Solar Module Phaesun PN6M120-380 C	8
Solar charge controller MPPT Victron SmartSolar 150/45	3
Solar charge controller MPPT Victron SmartSolar 100/20	1
AGM Battery Phaesun Sun Store 175Ah	8
Module structures	Optional
Cables, installation material	1
Remote Monitoring & Control Unit	Optional